

# HyFlex® 11-900

MECHANICAL PROTECTION



STYLE #	CONSTRUCTION	GAUGE	LINER MATERIAL	COATING MATERIAL	FINISHING	CUFF STYLE	COLOUR	EN SIZE	LENGTH MM	PACKAGING
11-900	Knitted	15	Nylon	Nitrile	Palm coated	Knitwrist	Blue and white	6, 7, 8, 9, 10	200 - 255	12 pairs in a bag, 12 bags in a carton



## Good dexterity and tactility in an oil-repellent glove

### PRIMARY INDUSTRIES



### IDEAL APPLICATIONS

- Assembly of white goods
- Brown goods
- Tools and power tools
- Light assembly tasks

### DESCRIPTION

- The HyFlex 11-900 industrial work glove provides light mechanical protection with dexterity.
- Designed specifically for use in moderately oily manufacturing and maintenance environments where protection combined with a dry only grip and abrasion resistance are essential.
- When workers need secure handling with comfort in these environments, the Ansell HyFlex 11-900 work glove delivers excellent results.

### REMARKS

- Antistatic according to EN1149
- Fit for special purpose
- Testing compliant to AS/NZS 2161



EN 388  
3131

**CATEGORY II**

Print date: 21-11-2013

**Ansell Healthcare Europe N.V. (European Head Office)**

Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium

Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03

<http://www.ansell.eu> • E-mail [info@ansell.eu](mailto:info@ansell.eu)

## Oil-Repellent

Print date 21-11-2013

**Glove material**

- Nitrile (Coating material)
- Nylon (Liner material)

**Possible Harmful ingredients**Sensitizers

- No sensitizers

Reach Regulation 1907/2006

For more information, please consult the REACH statement on the Ansell website

**Properties**

- Superior comfort due to the absence of seams in the inside of the gloves
- Superior flexibility and finger dexterity
- Good abrasion resistance
- Excellent dry grip

**EN Test Data****Abrasion resistance:**

Performance level 3

**Blade cut resistance:**

Performance level 1

**Tear resistance:**

Performance level 3

**Puncture resistance:**

Performance level 1

**European conformity**

Gloves conform to the requirements of the European Directive 89/686/EEC and to the European standards EN 420:2003 + A1:2009 and EN 388:2003

They are categorised in "Intermediate Design" (= Protection against intermediate risks).

EC-Type Examination Certificate for the final product by  
Centexbel  
Technologiepark 7  
B-9052 Zwijnaarde

**Application - Limitations of use**

Hand protection – light to medium duty applications

Do not use against flames or temperatures < - 25°C or > 100°C

Do not use against chemicals; the glove is not liquidproof

Do not use for heavy duty mechanical applications

**Storage**

Keep away from sources of ozone or ignition.

Keep out of direct sunlight; store in a cool and dry place.

Construction	Gauge	Liner material	Coating material	Finishing	Cuff style	Colour	EN Size	Length mm	Packaging
Knitted	15	Nylon	Nitrile	Palm coated	Knitwrist	Blue and white	6, 7, 8, 9, 10	200 - 255	12 pairs in a bag; 12 bags in a carton

The length of the gloves is below the EN requirements for total minimum glove length. Hence, the glove is called 'Fit for special purpose'

**Ansell Healthcare Europe N.V. (European Head Office)**

Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium

Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03

http://www.ansell.eu • E-mail info@ansell.eu

